

OBJECTIVE LENS DRIVE APPARATUS FOR USE IN OPTICAL PICKUP

Background of the Invention

The present invention relates to an objective lens drive
5 apparatus for use in an optical pickup forming an optical disk
unit which projects an optical spot onto a record medium to
be able to read information out of the record medium optically.

An optical pickup forming an optical disk unit is generally
composed of an objective lens drive apparatus including an
10 objective lens and an optical system for transmitting the light
to the objective lens and receiving the light therefrom, while
the objective lens drive apparatus is disposed on an optical
system block mounting table. The objective lens drive apparatus
is composed of a movable part including an objective lens,
15 a focus coil and a tracking coil, and a fixed part including
a magnetic circuit; and, the movable part is supported on the
fixed part by four wires each of which is in part surrounded
and held by an elastic damper member such as a visco-elastic
member.

20 As an objective lens drive apparatus which not only can
drive an objective lens in a focus direction and in a tracking
direction but also can correct the coma and astigmatism of
a spot which is image formed on a disk, there is known an apparatus
which is disclosed in Japanese Patent Publication No. Hei.
25 9-231595. This conventional device is characterized in that,

as shown in Figs. 24, 25 and 26, on the surface of a lens holder 1101 that is situated opposed to an optical disk, there are disposed at least a pair of optical sensors 1301, 1302 which extend in the optical disk radial direction or tangential direction of an objective lens 1103; on one or both of the side surfaces of the lens holder 1101 in the optical disk radial direction, there are disposed coils 1105 which are used to correct the inclination of the objective lens; and, on a pair of yokes 1113 and 1114 which are disposed opposed to the side surface of the lens holder 1101, there are disposed a pair of reversed-polarity magnet members 1106 and 1107 for correction of the inclination of the objective lens in such a manner that they correspond to the positions of the coils 1105, whereby the inclination of the objective lens with respect to an optical disk 1100 is detected in accordance with the outputs of the optical sensors 1301 and 1302. In accordance with the thus detected objective lens inclination angle and the calculated value of a shift between the optical axis of a collimator and the optical axis of the objective lens, currents are supplied to the coils 1105 for inclination correction to thereby drive the coils 1105 and, due to the electro-magnetic mutual reaction between the coils 1105 and the reversed polarity magnet members 1106 and 1107, the side surfaces of the lens holder 1101 are driven, so that the side surfaces of the lens holder 1101 can be servo controlled in a freely inclinable manner.

The pair of optical sensors 1301 and 1302 are respectively mounted on the two sides of the objective lens 1103 of the lens holder 1101 and, as shown in Fig. 25, are used to receive primary lights 1201, 1202 that are emitted from an optical head and diffracted by an optical disk groove. Electric signals from the optical sensors 1301, 1302, as shown in Fig. 27, are amplified by amplifiers 1407, 1408 and are then differentially input to a differential amplifier 1403. From the output of the differential amplifier 1403, there is calculated an inclination angle between the optical disk 1100 and lens holder 1101.

As shown in Fig. 27, from the thus calculated inclination angle and the shift between the objective lens optical axis and collimator optical axis, preferably, using a preset section 1404 set in a ROM (Read Only Memory), there is calculated a lens optimum inclination angle; and, based on the above two calculation results, the inclination correcting coils 1105 are driven through a phase compensation circuit 1405 and a drive amplifier 1406 for servo control.

Referring to the structure of the lens holder 1101, in the plane surface thereof, there are formed two slits 1102 through which their associated yoke members 1109 can be inserted respectively; on the central portion of the lens holder 1101, there is mounted the objective lens 1103; and, on a pair of mutually opposing side surfaces of the lens holder 1101, there

are disposed square-shaped flat coils 1104 for tracking drive by twos, a total of four coils 1104. Also, on the two mutually opposing surfaces of the lens holder 1101 in the optical disk radial direction (R), as the coils 1105 for inclination correction, there are disposed a pair of square-shaped flat coils; and, above and below the coils 1105 for inclination correction, there are disposed printed circuit boards (not shown) which are supported through copper foil portions 1115, 1116.

On an actuator base 1108, there are projectingly provided yoke portions 1109, 1110; and, the yoke portions 1109, 1110, through magnets 1111, 1112, form a substantially closed magnetic circuit for focus-direction and tracking-direction driving.

Also, on the two side surfaces of the actuator base 1108, there are disposed two side yokes 1113, 1114 for lens holder inclination adjustment drive, the top plan views of which respectively show a horseshoe shape. And, in each of the side yokes 1113, 1114, there are disposed long magnets 1106 and 1107 of mutually reversed polarities in such a manner that they correspond to the upper and lower sides of the coils 1105 for inclination correction.

Also, on the actuator base 1108, similarly to the above, there are further disposed square-shaped printed circuit boards 1117, 1118 through copper foil portions 1119, 1120. And, four spring wires 1121 of phosphor bronze are connected to the lens holder 1101 in such a manner that the spring wires 1121 are

respectively fixed by printed circuit boards disposed on the two ends of the spring wires 1121; and thus, the lens holder 1101 is supported elastically by the spring wires 1121 (as for the fixation of the spring wires 1121, see the plan view shown in Fig. 26).

In Fig. 24, reference character F designates a focus axis of a moving system of an objective lens actuator, R stands for a tracking axis thereof, and T represents an optical disk tangent axis thereof.

Next, description will be given below of the inclination drive of the lens holder 1101 according to the related art with reference to Fig. 25. In case where the current directions of the coils 1105 for right and left inclination correction respectively disposed on the optical-disk-radial-direction two side surfaces of the lens holder 1101 are set in the same direction and the magnetic field directions of the left and right magnets 1106 and 1107 disposed so as to correspond to the upper and lower sides of the coils 1105 for inclination correction are set symmetrical, the electromagnetic driving forces of the right and left coils are different in direction from each other according to Fleming's rule (see arrow marks F, F' in Fig. 25). Therefore, while the center of gravity or center of support of the lens holder 1101 is present substantially at the same point, in case where the lens holder 1101 is rotated about this point, the inclination of the objective lens with

respect to the optical disk 1100 can be corrected.

However, in the above-mentioned conventional technique, in order to correct the inclination of the objective lens, separately from the coils and magnets for tracking servo and focus servo, there must be further disposed the coils 1105 and magnets 1106, 1107 for inclination correction, which results in the increased cost of the objective lens drive apparatus.

Also, in the conventional technique, the coils 1105 and magnets 1106, 1107 for inclination correction must be disposed on the optical-disk-1100 radial direction side surfaces of the lens holder 1101 holding the objective lens 1103, which results in the increased width and weight of the objective lens drive apparatus.

Summary of the Invention

The present invention aims at solving the above problems found in the conventional technique.

Now, description will be given below of first aspect of the invention for solving the above problems with reference to Fig. 1 which corresponds to a first embodiment of the invention.

According to the first aspect, within the same magnetic gap S_g of a magnetic circuit having at least one magnet 5 magnetized in two polarities, there is disposed a coil unit 3 on which a focus coil 3f, tracking coils 3tr and tilt coils 3ti are mounted.

In the first aspect, the magnet 5 magnetized in two polarities is used to make a correction of the inclination of an objective lens, which can eliminate the need for provision of an exclusive magnet exclusively used to correct the
5 above-mentioned objective lens inclination.

Also, description will be given below of second aspect of the invention for solving the above problems with reference to Fig. 11 which corresponds to a second embodiment of the invention. According to the second the second aspect, there
10 are completed two magnetic circuits each having at least one magnet 105 magnetized in two polarities and, within the magnetic gap 105g of each of the two magnetic circuits, there is disposed a coil unit 103 on which a focus coil 103f, tracking coils 103tr and tilt coils 103ti are mounted.

15 In the second aspect, the magnet 105 magnetized in two polarities is used to make a correction of the inclination of an objective lens, which can eliminate the need for provision of an exclusive magnet exclusively used to correct the objective lens inclination.

20 Further, description will be given below of third aspect of the invention for solving the above problems with reference to Fig. 18 which corresponds to a third embodiment of the invention. According to the third aspect, there is provided an objective lens drive apparatus for use in an optical pickup which detects
25 the inclination of an optical disk and adjusts the inclination

of an objective lens in accordance with an optical disk inclination signal, wherein, within the same magnetic gap 205g of a magnetic circuit having at least one magnet 205 magnetized in two polarities, there is disposed a coil unit 203 on which
5 a plurality of focus coils 203fl, 203fr and tracking coils 203t are mounted. Currents are respectively supplied to the plurality of focus coils 203fl, 203fr and, due to the sum of the driving forces of the focus coils 203fl, 203fr, focus servo is executed. Due to the difference between the above driving
10 forces, there is produced moment around the center of gravity of a movable part and the inclination of the objective lens 202 can be thereby adjusted simultaneously with the focus servo operation.

In the third aspect, due to the operations of the plurality
15 of focus coils 203fl and 203fr, not only the focus servo but also the adjustment of the inclination of the objective lens 202 can be executed.

Brief Description of the Drawings

20 Fig. 1 is an exploded perspective view of a first embodiment of an objective lens drive apparatus for use in an optical pickup according to the invention;

Fig. 2 is a side view of a magnetic circuit employed in the first embodiment according to the invention;

25 Fig. 3 is an arrangement view of the first embodiment,

showing the position relationship between magnets and focus coils/tracking coils at the self-weight position of the first embodiment in the focus direction;

Fig. 4 is an arrangement view of the first embodiment,
5 showing the position relationship between magnets and tilt coils at the self-weight position of the first embodiment in the focus direction;

Fig. 5 is an arrangement view of a modification of the first embodiment, showing the position relationship between
10 magnets and tilt coils at the self-weight position of the modification in the focus direction;

Fig. 6 is a plan view of a magnetic circuit employed in the modification of the first embodiment;

Fig. 7 is an arrangement view of the modification, showing
15 the position relationship between magnets and focus coils/tracking coils at the self-weight position of the modification in the focus direction;

Fig. 8 shows of a modification of a coil unit of the first embodiment;

20 Fig. 9 is an exploded perspective view of another modification of the first embodiment;

Fig. 10 is a plan view of a magnetic circuit employed in the objective lens drive apparatus shown in Fig. 9;

Fig. 11 is an exploded perspective view of a second
25 embodiment of an objective lens drive apparatus for use in

an optical pickup according to the invention;

Fig. 12 is an exploded perspective view of a modification of the second embodiment;

Figs. 13A and 13B are plan views of a magnetic circuit
5 employed in the objective lens drive apparatus shown in Fig.
9;

Fig. 14 is an exploded perspective view of another modification of the second embodiment;

Fig. 15 is a front view of the objective lens drive apparatus
10 shown in Fig. 14;

Fig. 16 is an arrangement view of the modification of
the second embodiment shown in Fig. 14, showing the position
relationship between magnets and tracking coils/tilt coils
at the self-weight position of the first embodiment in the
15 focus direction;

Fig. 17 is an arrangement view of the modification of
the second embodiment shown in Fig. 14, showing the position
relationship between magnets and tracking coils/tilt coils
at the self-weight position of the first embodiment in the
20 focus direction;

Fig. 18 is an exploded perspective view of a third embodiment
of an objective lens drive apparatus for use in an optical
pickup according to the invention;

Fig. 19 is an arrangement view of the third embodiment,
25 showing the position relationship between magnets and focus

coils/tracking coils at the self-weight position of the third embodiment in the focus direction;

Fig. 20 is a block diagram of a circuit configuration for focus servo and inclination drive employed in the third embodiment of the invention;

Fig. 21 is an explanatory view of the focus servo and inclination drive to be executed in the third embodiment; specifically, Fig. 16A shows a case where there are produced driving forces having the same direction; and, Fig. 16B shows a case where there are produced driving forces respectively having reversed directions;

Fig. 22 is an exploded perspective view of a modification of the third embodiment;

Fig. 23 is an arrangement view of the modification of the third embodiment, showing the position relationship between magnets and focus coils/tracking coils at the self-weight position of the modification in the focus direction;

Fig. 24 is an exploded perspective view of a conventional objective lens drive apparatus;

Fig. 25 is an explanatory view of an inclination correction driving operation to be executed in the conventional objective lens drive apparatus;

Fig. 26 is a plan view of an actuator employed in the conventional objective lens drive apparatus; and,

Fig. 27 is a block diagram of the configuration of a circuit

employed in the conventional objective lens drive apparatus to execute the inclination correction driving operation.

Detailed Description of the Preferred Embodiments

5 (Embodiment 1)

Now, Fig. 1 is an exploded perspective view of a first embodiment of an objective lens drive apparatus for use in an optical pickup according to the invention. In Fig. 1, reference character 1 designates a lens holder, 2 an objective lens, 3 a coil unit, 3f a focus coil, 3tr a tracking coil, 3ti a tilt coil, 5 a magnet, and 5g a magnetic gap, respectively.

The lens holder 1 is formed of light metal of high modulus of flexural elasticity, for example, magnesium alloy, or resin mixed with carbon fibers. Use of such material allows the lens holder 1 itself to have higher flexural elasticity modulus and thus have higher high-order resonance frequencies. Due to this, the lens holder 1 is able to cope with an increase in the speed of an optical disk unit.

In the lens holder 1, there are formed two notch portions 1a which respectively extend in the tracking direction T. Also, an objective lens mounting portion 1b, which is also formed in the lens holder 1, is structured such that it is uniform in thickness.

Each of the two notch portions 1a has a surface on which there is formed an insulated protective film (not shown) for

insulation reinforcement. The reason for provision of such insulated protective film is that, since light metal of high flexural elasticity modulus such as magnesium alloy or resin mixed with carbon fibers used as the material of the lens holder 1 is high in conductivity, the insulation of the coil unit 3 to be mounted on the notch portions 1a must be secured. In case where an insulated protective film for insulation reinforcement is not formed on the surfaces of the notch portions 1a of the lens holder 1, an insulated protective film (not shown) for insulation reinforcement may be formed on the portions of the coil unit 3 that are to be mounted onto the notch portions 1a to thereby be able to secure the insulation of the coil unit 3.

The coil unit 3 is a laminated coil unit which comprises: a required number of printed circuit boards 31 each having a pattern in which a focus coil 3f and four tracking coils 3tr are formed; and, a required number of printed circuit boards 32 in each of which two tilt coils 3ti are formed, whereby the two kinds of printed circuit boards 31 and 32 are alternately laminated one on top of another to thereby provide a pattern structure as a coil unit. The focus coil 3f is disposed in the central portion of the printed circuit board 31; and, the tracking coils 3tr are disposed right and left (in the tracking coil direction T) with respect to the position of the center of gravity of an objective-lens-optical-axis-direction movable

part including the lens holder 1 holding the objective lens 2, that is, on the right and left sides of the focus coil 3f in two upper and lower stages. The four tracking coils 3tr are connected in series. By the way, the tracking coils 3tr may also be composed of two tracking coils. The two tilt coils 3ti are disposed right and left (in the tracking coil direction T) with respect to the center of the printed circuit board 32. The two tilt coils 3ti are connected in series.

The printed circuit boards 31 and 32 can be laminated one on top of another, for example, by holding the two side surfaces of a printed circuit board 32 between two printed circuit boards 31 in such a manner that they are arranged symmetric when they are viewed from the tracking direction T. In this case, drive points in the respective directions can be made coincident, thereby being able to avoid resonance (pitching resonance, yawing resonance) which would be possibly caused when the drive points are not coincident.

The foregoing description relates to the structure where the focus coil 3f and tracking coils 3tr are formed in each printed circuit board 31. However, the focus coil 3f and tracking coils 3tr may also be formed separately in two printed circuit boards. Further, as shown in Fig. 8, the coil unit 3' may have a printed circuit board 31' and a printed circuit board 32', wherein the focus coil 3f and tilt coils 3ti are formed on the printed circuit board 31', and the tracking coils 3tr are

formed on the printed circuit board 32'. Fig. 8 shows four tracking coil 3ti are formed on the printed circuit board 32', however, two tracking coil 3ti may be formed on the printed circuit board 32'. In these structures as well, the printed circuit boards may be laid one on top of another so as to be symmetric right and left when they are viewed from the tracking direction T, thus being able to avoid resonance by possibly caused when the drive points are not coincident.

The coil unit 3 is inserted into and bonded to the notch portions 1a so that it is fixed to the lens holder 1. In the two ends of the coil unit 3 in the tracking direction T, there are formed six V-grooves 3v, while one-end portions of six conductive elastic members 4 are respectively fixed by solder (not shown) to the six V-grooves 3v. In the case of the conductive elastic members 4 which serve as lead wires, two of them are used to drive the focus coils, two are used to drive the tracking coils, and two are used to drive the tilt coils: that is, a total of six conductive elastic members are provided. By the way, four conductive elastic members 4 are sufficient to elastically hold the lens holder 1 which serves as a movable part and, therefore, in case where four conductive elastic members 4 are used, lead wires (not shown) are to be connected to the remaining coils.

The magnet 5 is bonded to a yoke 7 disposed on a yoke base 6 in such a manner that the magnet 5 is magnetized in

two polarities in the focus direction F by a boundary line 5b between the N and S poles of the magnet 5. As shown in Fig. 2, the boundary line 5b between the N and S poles is positioned at the center of the magnet 5 in the focus direction F, the mutually opposing arrangement of two magnets 5 forms a magnetic gap 5g between them, and, magnetic force lines B are reversed in direction in the focus direction F of the magnetic gap 5g.

By the way, as shown in Fig. 9, the magnetic circuit may include one magnet 5', and the coil unit may be disposed in the magnetic gap 5g'. Fig. 10 shows the magnetic circuit including the magnet 5', similar operation of coils in the case of providing the magnetic circuit including two magnets 5 and gap 5g described above can be obtained. Due to this, the whole objective lens drive apparatus can be made compact. Here, the magnetic gap means an air gap or an air path, in Fig. 9, the magnetic gap 5g' is formed by one magnet.

The width W of the magnet 5 is determined such that when the coil unit 3, as shown in Fig. 3, is disposed in the magnetic gap 5g at the movable neutral position of the movable part which is movably supported in a cantilevered manner by the conductive elastic members 4, that is, at the self-weight position of the movable part in the focus direction F, of the vertical sides A and C (which extend in parallel to the focus direction F) of the four tracking coils 3tr disposed right and left in the two upper and lower stages, the right and left inner vertical

sides A and C can be disposed within the magnetic gap 5g (which points out a gap existing within the width W of the two mutually opposing magnets 5); and also, as shown in Fig. 4, of the vertical sides a' and c' (which extend in parallel to the focus direction F) of the two tilt coils 3ti disposed right and left in a row, the right and left outer vertical surfaces a' and c' can be disposed within the magnetic gap 5g. Also, the height H of the magnet 5 is determined such that, as shown in Fig. 3, the horizontal sides b and d (which extend perpendicularly to the focus direction F) of the single focus coil 3f disposed at the center of the printed circuit board 31 as well as the upper and lower outer horizontal sides B and D of the horizontal sides B and C (which extend perpendicularly to the focus direction F) of the tracking coils 3tr can be disposed within the magnetic gap 5g (which points out a gap existing within the height H of the two mutually opposing magnets 5); and also, as shown in Fig. 4, the horizontal sides b' and d' (which extend perpendicularly to the focus direction F) of the tilt coils 3ti can be disposed within the magnetic gap 5g.

The boundary line 5b between the N and S poles of the magnet 5, as shown in Fig. 3, is situated midway between the lower side b and upper side d of the horizontal sides b, d (which extend perpendicularly to the focus direction F) of the focus coil 3f, midway between the lower side B of the horizontal sides B, D (which extend perpendicularly to the focus direction

F) of the upper-stage tracking coil 3tr and the upper side D of the horizontal sides B, D (which extend perpendicularly to the focus direction F) of the lower-stage tracking coil 3tr, and, as shown in Fig. 4, midway between the lower side b' and upper side d' of the horizontal sides b', d' (which extend perpendicularly to the focus direction F) of the tilt coils 3ti. The center of the magnet 5 is substantially coincident with the center of the coil unit 3.

In Fig. 3, in case where currents are allowed to flow in the tracking coils 3tr, due to the currents (shown by arrow marks) that flow in the vertical sides A, C which extend in parallel to the focus direction F) of the tracking coils 3tr, in the four tracking coils 3tr, there are generated driving forces in the same direction according to Fleming's left-hand rule. Also, in case where a current is allowed to flow in the focus coil 3f, due to the currents that flow in the horizontal sides b, d (which extend perpendicularly to the focus direction F) of the focus coil 3f, in the focus coil 3f, there is generated a driving force in the focus direction F according to Fleming's left-hand rule.

In Fig. 4, in case where currents are allowed to flow in the tilt coils 3ti, due to the currents (shown by arrow marks) that flow in the horizontal sides b', d' (which extend perpendicularly to the focus direction F) of the tilt coils 3ti, in the two tilt coils 3ti, there are generated driving

forces F' in the mutually reversed directions in the focus direction F according to Fleming's left-hand rule. Due to the mutually-reversed-direction driving forces F' , there is generated moment around the center of gravity of the movable
5 part to thereby be able to adjust the inclination of the lens holder 1 and thus the inclination of the objective lens 2.

As described above, in case where not only the focus coil $3f$ and tracking coils $3tr$ but also the tilt coils $3ti$ are arranged within the same magnetic gap $5g$ of the magnetic circuit including
10 at least one magnet, not only focus servo and tracking servo but also tilt servo (that is, the adjustment of the inclination of the objective lens 2) can be carried out. This can eliminate the need for provision of a magnet which is exclusively used to adjust the inclination of the objective lens 2. Due to this,
15 the number of parts can be reduced, the adjustment of the inclination of the objective lens 2 can be made at a low cost, and the whole objective lens drive apparatus can be made compact.

The foregoing description relates to the structure in which the two tilt coils $3ti$ are arranged right and left (in
20 the tracking direction T) with respect to the center of the printed circuit board 32. However, a similar effect can also be obtained even in a structure in which, as shown in Fig. 5, two tilt coils $3ti$ are arranged upward and downward (in the focus direction F) with respect to the center of the printed
25 circuit board 32.

In this case, the coil unit 3 is structured such that, as shown in Fig. 7, a required number of printed circuit boards (not shown) each having a pattern including a tracking coil 3tr and four focus coils 3f and, as shown in Fig. 5, a required number of printed circuit boards (not shown) each having a pattern including two tilt coils 3ti are alternately laid one on top of another.

The foregoing description relates to the structure in which the focus coil 3f and tracking coils 3tr are disposed on the same printed circuit board. However, there can also be employed a structure in which focus coils 3f and tracking coils 3tr are separately disposed on two printed circuit boards.

In this case as well, the printed circuit boards are laid one on top of another so as to be symmetric right and left when they are viewed from the tracking direction T.

In this structure, the magnet 5, as shown in Fig. 6, is magnetized in two polarities in the tracking direction T by the boundary line 5b between the N and S poles of the magnet 5, and is bonded to the yoke 7 on the yoke base 6. As shown in Fig. 6, the boundary line 5b between the N and S poles is situated at the center of the magnet 5 in the tracking direction T, the magnetic gap 5g is formed due to the mutually opposing arrangement of the two magnets 5 and, in the magnetic gap 5g, the direction of a magnetic line of force B is reversed in the tracking direction T. By the way, alternatively, as shown

in Figs. 9 and 10, instead of the two magnets 5, there may be used a single magnet 5. In this case, the boundary line 5b' between the N and S poles is situated at the center of the magnet 5 in the tracking direction T. Due to this, the whole objective lens drive apparatus can be made compact.

The width W of the magnet 5 is determined such that, as shown in Fig. 7, when the coil unit 3 is arranged in the magnetic gap 5g at the movable neutral position of the movable part movably supported in a cantilevered manner by the conductive elastic members 4, that is, at the self-weight position thereof in the focus direction F, not only the right and left outer vertical sides a and c of the vertical sides a and c (which extend in parallel to the focus direction F) of the four focus coils 3f arranged right and left in two upper and lower stages but also, as shown in Fig. 5, the vertical sides a' and c' (which extend in parallel to the focus direction F) of the two tilt coils 3ti arranged in two upper and lower stages can be respectively disposed within the magnetic gap 5g (which points out a gap existing within the width W of the mutually opposing magnets 5). Also, the height H of the magnets 5 is determined such that not only, as shown in Fig. 7, the lower sides b of the horizontal sides b, d (which extend perpendicularly to the focus direction F) of the upper-stage focus coils 3f, the upper sides d of the horizontal sides b, d (which extend perpendicularly to the focus direction F) of the lower-stage

focus coils 3f, and the horizontal sides B and D (which extend perpendicularly to the focus direction F) of the tracking coil 3tr but also, as shown in Fig. 5, the upper sides d' of the horizontal sides b', d' (which extend perpendicularly to the focus direction F) of the upper-stage tilt coil 3ti and the lower sides b' of the horizontal sides b', d' (which extend perpendicularly to the focus direction F) of the lower-stage tilt coil 3ti can be respectively disposed within the magnetic gap 5g (which points out a gap existing within the height H of the mutually opposing magnets 5).

The boundary line 5b between the N and S poles of the magnet 5 is situated not only, as shown in Fig. 7, midway between the left sides c of the vertical sides a, c (which extend in parallel to the focus direction F) of the right focus coil 3f and the right sides a of the vertical sides a, c (which extend in parallel to the focus direction F) of the left focus coil 3f, and midway between the right side A and left side C of the vertical sides A, C (which extend in parallel to the focus direction F) of the tracking coil 3tr, but also with, as shown in Fig. 5, midway between the right side a' and left c' of vertical sides a', c' (which extend in parallel to the focus direction F) of the tilt coil 3ti. The center of the magnet 5 is substantially coincident with the center of the coil unit 3.

In Fig. 7, in case where a current is allowed to flow

in the tracking coil 3tr, due to the current (shown by an arrow mark) that flows in the vertical sides A, C (which extend in parallel to the focus direction F) of the tracking coil 3tr, in the tracking coil 3tr, there is generated a driving force in the tracking direction T according to Fleming's left-hand rule; and, in case where currents are allowed to flow in the focus coils 3f, due to the currents (shown by arrow marks) that flow in the horizontal sides b, d (which extend perpendicularly to the focus direction F) of the focus coils 3f, in the four focus coils 3f, there are generated driving forces respectively having the same direction in the tracking direction T according to Fleming's left-hand rule.

In Fig. 5, in case where currents are allowed to flow in the tilt coils 3ti, due to the currents (shown by arrow marks) that flow in the vertical sides a', c' (which extend in parallel to the focus direction F) of the tilt coils 3ti, in the two tilt coils 3ti, there are generated driving forces in the mutually reversed directions in the tracking direction T according to Fleming's left-hand rule. Due to the reversed-direction driving forces, there is generated moment around the center of gravity of the movable part to thereby be able to adjust the inclination of the lens holder 1 and thus the inclination of the objective lens 2.

(Embodiment 2)

Now, Fig. 11 is a perspective view of a second embodiment

of an objective lens drive apparatus according to the invention.

In Fig. 11, reference character 101 designates a lens holder, 102 an objective lens, 103 a coil unit, 103f a focus coil, 103tr a tracking coil, 103ti a tilt coil, 105 a magnet, and 105g a magnetic gap, respectively.

The lens holder 101 is made of light metal of high modulus of flexural elasticity, for example, magnesium alloy, or resin mixed with carbon fibers. Use of such material allows the lens holder 101 itself to have higher flexural elasticity modulus and thus have higher high-order resonance frequencies. Due to this, the lens holder 101 is able to cope with an increase in the speed of an optical disk unit.

Referring further to the structure of the lens holder 101, on the plane surface thereof, there are formed two slits 111 through which a magnet 105 and a yoke 107 (both of which will be discussed later) can be inserted; on the central portion of the lens holder 101, there is mounted the objective lens 102; on each of a pair of side surfaces of the lens holder 101 which extend at right angles to the tracking direction T, there are projectingly disposed two upper and lower support pieces 112 to which the one-end portions of conductive elastic members 104 (which will also be discussed later) can be fixed; and, to a pair of side surfaces of the lens holder 101 which extend in parallel to the tracking direction T, there are fixed coil units 103 (which will also be discussed later).

Insulated protective films (not shown) for reinforcement are respectively formed on the surfaces of the pair of side surfaces (which extend in parallel to the tracking direction T) of the lens holder 101. The reason for provision of such insulated protective films is to secure the insulation of the coil units 103 to be mounted onto the lens holder 101 because light metal of high modulus of flexural elasticity, for example, magnesium alloy, or resin mixed with carbon fibers used as the material of the lens holder 101 is high in conductivity.

In case where such insulated protective films for reinforcement are not formed on the surfaces of the pair of side surfaces (which extend in parallel to the tracking direction T) of the lens holder 101, insulated protective films (not shown) for reinforcement may be formed on the portions of the coil units 103 that are to be mounted onto the lens holder 101, thereby securing the insulation of the coil units 103.

Referring now to the coil unit 103, a required number of printed circuit plates 131 each having a pattern composed of a focus coil 103f and four tracking coils 103tr and a required number of printed circuit plates 132 each having a pattern composed of two tilt coils 103ti are laminated or laid one on top of another to thereby form the coil unit 103. The focus coil 103f is disposed in the central portion of the printed circuit board 131; and, the tracking coils 103tr are disposed in the right and left directions (in the tracking direction

T) with respect to the position of the center of gravity of an objective-lens-optical-axis-direction movable part including the lens holder 101 holding the objective lens 102, that is, on the right and left sides of the focus coil 103f in two upper and lower stages. The four tracking coils 103tr are connected in series. By the way, the four tracking coils 103tr may also be replaced with two tracking coils. The two tilt coils 103ti are disposed in a row right and left (in the tracking coil direction T) with respect to the center of the printed circuit board 32. The two tilt coils 103ti are connected in series.

The printed circuit boards 131 and 132 may be laminated in such a manner that the two side surfaces (which extend in parallel to the tracking direction T) of the printed circuit board 131 and the two side surfaces (which extend in parallel to the tracking direction T) of the printed circuit board 132 are arranged symmetric when they are viewed from the tracking direction T, for example, the printed circuit board 131 is arranged inside on the objective lens 102 side and the printed circuit board 132 is arranged outside on the objective lens 102 side. In this case, drive points in the respective directions can be made coincident with each other, thereby being able to avoid resonance (pitching resonance, yawing resonance) which would be possibly caused when the drive points are not coincident.

The foregoing description relates to the structure in

which the focus coil 103f and tracking coils 103tr are formed in the same printed circuit board 131. However, the focus coil 3f and tracking coils 3tr may also be formed separately in two different printed circuit boards. Further, as shown in Fig. 8, the coil unit 3' may have a printed circuit board 31' and a printed circuit board 32', wherein the focus coil 3f and tilt coils 3ti are formed on the printed circuit board 31', and the tracking coils 3tr are formed on the printed circuit board 32'. Fig. 8 shows four tracking coil 3ti are formed on the printed circuit board 32', however, two tracking coil 3ti may be formed on the printed circuit board 32'. In these case as well, the printed circuit boards may be laid one on top of another symmetrically right and left when they are viewed from the tracking direction T, thus being able to avoid resonance by possibly caused when the drive points are not coincident.

The one-end portions of the four conductive elastic members 104 are respectively fixed by solder (not shown) to the support pieces 112 of the lens holder 101 with the coil units 103 fixed thereto. Two lead wires are necessary to drive the focus coils, two lead wires are necessary to drive the tracking coils, and two lead wires are necessary to drive the tilt coils, that is, a total of six lead wires are necessary. Here, four units of such conductive elastic member 104 are enough to elastically support the lens holder 101 serving as the movable part. Here, the conductive elastic members 104 can also be used as lead

wires. Therefore, the four conductive elastic members 104 are used as four of the six lead wires, while other lead wires (not shown) are connected to the remaining coils.

The two coil units 103 are respectively arranged in the two magnetic gaps 105g, while the other-end portions of the conductive elastic members 104 are respectively penetrated through a wire base 108 and are fixed to a base plate 109 by soldering. Due to this, the focus coil 103f, tracking coils 103tr and tilt coils 103ti mounted on the coil unit 103 can be disposed within the magnetic gap 105g and, at the same time, the movable part including the lens holder 101 holding the objective lens 2 is supported in a cantilevered manner so as to be movable with respect to the fixed part which includes the magnet 105, yoke base 106, yoke 7, wire base 108 and base plate 109.

The structures of the magnetic circuits employed in the apparatus shown in Fig. 11 as well as the arrangements and operations of the focus coils, tracking coils and tilt coils used in the coil units of the apparatus shown in Fig. 11 are similar to the previously described first embodiment and thus the description thereof is omitted here (see Figs. 2 to 4).

As described above, according to the present embodiment, there are completed two magnetic circuits each including at least one magnet 105 magnetized in two polarities, and, within the magnetic gap 105g of each of the two magnetic circuits

105, there are disposed not only the focus coil 103f and tracking coils 103tr but also the tilt coils 103ti. Thanks to this, not only focus servo and tracking servo but also tilt servo (that is, the adjustment of the inclination of the objective lens 102) can be attained. Therefore, there is eliminated the need for provision of a magnet which is exclusively used to adjust the inclination of the objective lens 102. This can reduce the number of parts, can adjust the inclination of the objective lens 102 at a low cost, and can reduce the size of the whole objective lens drive apparatus.

The above description relates to the structure in which the two tilt coils 103ti are respectively disposed right and left (in the tracking direction T) with respect to the center of the printed circuit board 132. However, similarly to the first embodiment, even in case where the two tilt coils 103ti are respectively disposed upwardly and downwardly (in the focus direction F) of the center of the printed circuit board 132, there can be obtained a similar effect. In this case, the structure of the magnetic circuit and the operation of the coil unit are similar to the first embodiment and thus the description thereof is omitted here (see Figs. 5 to 7). By the way, as shown in Fig. 12, two magnetic circuits may respectively include one magnet 105'. In this case, magnets 105' and yokes 107' are respectively provided outside of a lens holder 101' with respect to the center of the lens holder

101'. In this structure, the slit 111 need not be provided in the lens holder 101', therefore, the whole objective lens drive apparatus can be made compact. The magnetic circuit in this case is shown in Figs. 13A or 13B. Here, the magnetic gap means an air gap or air path. In Fig. 13A, the magnetic gap 105g' is formed by two magnets, and in Fig. 13B, the magnetic gaps 105g' are respectively formed by each magnet.

In the above structure, the coil units 103 are bonded and fixed to the pair of side surfaces of the lens holder 101 that extend in parallel to the tracking direction. However, a similar effect can also be obtained even in another structure in which, as shown in Fig. 14, there are completed two magnetic circuits each including at least one magnet 105 magnetized in two polarities in the focus direction F and, within each of the magnetic gaps 105g of the magnetic circuits, there are disposed focus coils 130f respectively wound around the side surfaces of the lens holder 101 as well as the tracking coils 130tr and tilt coils 130ti respectively mounted on the two side surfaces (which extend in parallel to the tracking direction T) of the lens holder 101. By the way, two magnetic circuit may be respectively include one magnet, as shown in Fig. 12.

Each focus coil 130f is a winding coil with the lens holder 101 as its winding frame and thus, when compared with a focus coil which is pattern formed on a printed circuit board, the focus coil 130f is easy to manufacture.

The tracking coil 130tr and tilt coil 130ti are respectively a coreless coil which is mounted on top of the focus coil 130f.

However, the tracking coil 130tr and tilt coil 130ti may also be pattern formed on a printed circuit board. Also, the tracking

5 coils 130tr and tilt coils 130ti may also be winding coils in which, as shown in Fig. 15, coil winding frames 113 are provided on and projected from the side surfaces (which extend in parallel to the tracking direction T) of the lens holder 101 and coils are respectively wound around these coil winding frames 113. Further, one of the tracking coil 130tr and tilt coil 130ti may be mounted on the focus coil 130f and the other may be wound around the coil winding frame 113.

10 The magnet 105 is magnetized in two polarities in the focus direction F by the boundary line 105b between the N and S poles of the magnet 105 and is bonded to the yoke 107 which is disposed on a yoke base 106.

15 The width W of the magnet 105 is determined such that, when, at the movable neutral position of the movable part movably supported in a cantilevered manner by the conductive elastic members 104, that is, at the self-weight position of the movable part in the focus direction F, as shown in Fig. 16, the lens holder 101 is arranged in the magnetic gap 105g, not only the right and left inner vertical sides A and C of the vertical sides A and C (which extend in parallel to the focus direction F) of the two tracking coils 130tr, which are disposed in the

20

25

upper stage in the focus direction F as well as are disposed right and left in a row in the tracking direction T, but also the right and left outer vertical sides a' and c' of the vertical sides a' and c' (which extend in parallel to the focus direction F) of the two tilt coils 130tr which are disposed in the lower stage in the focus direction F as well as are disposed right and left in a row in the tracking direction T can be respectively arranged within the magnetic gap 105g (which points out a gap existing within the width W of the two mutually opposing magnets 105). Also, the height H of the magnet 105 is determined such that, as shown in Fig. 16, the horizontal sides B and D (which extend perpendicularly to the focus direction F) of the tracking coils 130tr as well as the horizontal sides b' and d' (which extend perpendicularly to the focus direction F) of the tilt coils 130ti can be respectively disposed within the magnetic gap 105g (which points out a gap existing within the height H of the two mutually opposing magnets 105).

The boundary line 105b between the N and S poles of the magnet 105, as shown in Fig. 16, is situated downwardly of the lower sides B of the horizontal sides B and D (which extend perpendicularly to the focus direction F) of the tracking coils 130tr as well as midway between the lower sides b' and upper sides d' of the horizontal sides b' and d' (which extend perpendicularly to the focus direction F) of the tilt coils 130ti. The center of the magnet 105 is substantially coincident

with the center of the lens holder 101.

The focus coils 130f are disposed upwardly and downwardly with the boundary line 105b between the N and S poles of the magnet 105 as the boundary line thereof. The upper and lower
5 focus coils 130f are connected in series, while the directions of the currents of the upper and lower focus coils 130f are reversed. The directions of magnetic lines of force in the two magnetic gaps 105g are reversed.

In Figs. 14 and 15, all sides of the tracking coils 130tr
10 and tilt coils 130ti are mounted on one side surface (which extends in parallel to the tracking direction T) of the lens holder 1. However, this is not limitative but it is also possible to employ another structure; that is, the sides that are arranged within the magnetic gap 105g and are able to generate drive
15 forces, for example, the vertical sides A, C (see Fig. 16) (which extend in parallel to the focus direction F) of the tracking coils 130tr, which, in case where currents are allowed to flow in the tracking coils 130tr, can generate drive forces in the same direction in the tracking direction T, are mounted
20 on one side surface of the lens holder 1.

The lens holder 101 is disposed in the two magnetic gaps 105g and the other-side ends of the conductive elastic members 104 are penetrated through a wire base 108 and are fixed to a base plate 109 by soldering. Thanks to this, the focus coils
25 130f, tracking coils 130tr and tilt coils 130ti can be disposed

within the magnetic gap 105g and, at the same time, the movable part including the lens holder 101 holding the objective lens 102 can be supported in a cantilevered manner so as to be movable with respect to the fixed part which includes the magnet 5,
5 yoke base 106, yoke 107, wire base 108 and base plate 109.

In Fig. 14, in case where currents are allowed to flow in the focus coils 130f, due to the current that flows in the magnetic gap 105g, in the focus coils 130f, there are generated drive forces in the focus direction F according to Fleming's
10 left-hand rule.

In Fig. 16, in case where current are allowed to flow in the tracking coils 130tr, due to the currents (shown by arrow marks) that flow in the vertical sides A and C (which extend in parallel to the focus direction F) of the tracking
15 coils 130tr, in the two tracking coils 130tr, there are generated drive forces in the same direction in the tracking direction T according to Fleming's left-hand rule; and, in case where currents are allowed to flow in the tilt coils 130ti, due to the currents (shown by arrow marks) that flow in the horizontal
20 sides b' and d' (which extend perpendicularly to the focus direction F) of the tilt coils 130ti, in the two tilt coils 130ti, there are generated drive forces F' in the mutually reversed directions in the focus direction F according to Fleming's left-hand rule. Due to the reversed-direction drive
25 forces F', there is generated moment around the center of gravity

of the movable part, thereby being able to adjust the inclination of the lens holder 101 and thus the inclination of the objective lens 102.

The above description relates to the structure in which the two tracking coils 130tr and two tilt coils 130ti are arranged right and left symmetrically in the tracking direction T, while there are generated the drive forces in the same direction in the two tracking coils 130tr and there are generated drive forces in the reversed directions in the two tilt coils 130ti.

However, as shown in Fig. 17, the vertical side A (which extends in parallel to the focus direction F) of a tracking coil 130tr may be disposed within the width W of the magnet 105, and the vertical side C (which extends in parallel to the focus direction F) of the tracking coil 130tr may be disposed outside the width W of the magnet 105; and, at the same time, a tilt coil 130ti may be disposed shifted outside with respect to the center of the magnet 105 in the tracking direction T. Also, instead of the tracking coil 130tr, as shown in Fig. 16, there may be used two tracking coils 130tr; and, instead of the tilt coil 130ti, as shown in Fig. 17, there may be used two tilt coils 130ti. Further, the tracking coil 130tr, as shown in Fig. 17, may be one in number and the tilt coil 130ti, as shown in Fig. 16, may be two in number. In any of these structures, the weight of the objective lens drive apparatus can be reduced.

(Embodiment 3)

Now, Fig. 18 is a perspective view of a third embodiment of an objective lens drive apparatus according to the invention.

In Fig. 18, reference character 201 designates a lens holder, 202 an objective lens, 203 a coil unit, and 205 a magnet, respectively.

The lens holder 201 is similar in structure to the lens holder 1 employed in the previously described first embodiment.

The coil unit 203 comprises a required number of printed circuit boards 203p which are laminated one on top of another, while each of the printed circuit board 203p comprises a tracking coil 203t and four focus coils 203fl and 203fr. The tracking coil 203t is situated at the center of the printed circuit board 203p, while the focus coils 203fl and 203fr are arranged in two upper and lower stages and are disposed right and left with respect to the position of the objective-lens-optical-axis-direction center of gravity of a movable part including the lens holder 201 holding the objective lens 202, that is, on the right and left sides of the tracking coil 203t. The number of the focus coils 203fl and the number of the focus coils 203fr may also be one respectively. And, since currents are supplied to the left and right focus coils 203fl and 203fr individually, the left and right focus coils 203fl and 203fr are not connected in series but they are independent of each other.

The foregoing description relates to the structure in

which the left and right focus coils 203fl, 203fr and tracking coil 203t are disposed on the same printed circuit board 203p.

However, as a modification of the third embodiment, the left and right focus coils 203fl, 203fr and tracking coil 203t may also be disposed separately on two printed circuit boards. In this modification as well, the number of focus coils to be disposed on a printed circuit board is even and the number of tracking coils to be disposed on a printed circuit board is one.

The coil unit 203 is inserted into and bonded to the notch portions 201a of the lens holder 201 and is thereby fixed to the lens holder 201. In the two ends (in the tracking direction T) of the coil unit 203, there are formed six V-grooves 203v, while the one-side ends of six conductive elastic members 204 are respectively fixed to the six V-grooves 203v by solders 203h. The conductive elastic members 204, which are used as lead wires, consist of four members 204 (2 x 2) for focus coil driving and two members 204 for tracking coil driving, a total of six members 204.

By the way, four conductive elastic members 204 are enough to elastically hold the lens holder 201 serving as the movable part and, therefore, in case where four conductive elastic members 204 are employed to hold the lens holder 201, lead wires (not shown) are to be connected to the remaining coils.

The magnetic circuit employed in the present embodiment

is similar to the magnetic circuit employed in the first embodiment and shown in Fig. 6. Further, the magnetic circuit may be include one magnet, as shown in Figs. 9 and 10. In this case, the boundary line between the N and S poles is situated at the center of the magnet 5 in the tracking direction T as well as Fig. 6. Due to this, the whole objective lens drive apparatus can be made compact. The width W of the magnet 205 is determined such that, at the movable neutral position of the movable part movably supported in a cantilevered manner by the conductive elastic members 204, that is, at the self-weight position of the movable part in the focus direction F, as shown in Fig. 19, when the coil unit 203 is arranged within the magnetic gap 205g, the right and left outer vertical sides c and a (which extend in parallel to the focus direction F) of the vertical sides a and c of the left focus coils 203fl in the two upper and lower stages as well as the right focus coils 203fr in the two upper and lower stages can be respectively disposed within the magnetic gap 205g (which points out a gap existing within the width W of the mutually opposing magnets 205). Also, the height H of the magnet 205 is determined such that, as shown in Fig. 19, the lower sides b of the horizontal sides b and d (which extend perpendicularly to the focus direction F) of the upper-stage focus coils 203fl and 203fr, the upper sides d (which extend perpendicular to the focus direction F) of the lower-stage focus coils 203fl and 203fr, and the

horizontal sides B and D (which extend perpendicularly to the focus direction F) of the tracking coil 203t can be respectively disposed within the magnetic gap 205g (which points out a gap existing within the height W of the mutually opposing magnets 205).

The boundary line 205b between the N and S poles of the magnet 205, as shown in Fig. 19, is situated midway not only between the vertical sides A and C (which extend in parallel to the focus direction F) of the tracking coil 203t but also between the right sides a of the vertical sides a, c (which extend in parallel to the focus direction F) of the left focus coils 203fl and the left sides c of the vertical sides a, c (which extend in parallel to the focus direction F) of the right focus coils 203fr. The center of the magnet 205 is substantially coincident with the center of the coil unit 203.

The coil units 203 are respectively disposed within the magnetic gap 205g and the other-side ends of the conductive elastic members 204 are respectively penetrated through the wire base 208 and are fixed to the base plate 209 by soldering.

In this manner, the focus coils 203fl, 203fr and tracking coil 203t mounted on the coil unit 203 are disposed within the magnetic gap 205g and, at the same time, the movable part including the lensholder 201 supporting the objective lens 202 is supported in a cantilevered manner so as to be movable with respect to the fixed part which includes the magnets 205, yoke base 206,

yokes 207, wire base 208, and base plate 209.

The inclination of the optical disk can be detected using an inclination detect sensor which is separately prepared, or using a reproduction signal given by an optical pickup.

5 A tilt error signal and a focus error signal, which have been obtained using the inclination detect sensor or using the reproduction signal of the optical pickup, are input to a control circuit shown in Fig. 20; and, the control circuit calculates the optimum currents I_l and I_r which can urge the
10 focus coils 203fl and 203fr shown in Fig. 19 to thereby correct the focus error and tilt error at the same time, and then the control circuit outputs the thus calculated currents I_l and I_r . The objective lens drive apparatus, which is a controlled object, not only executes a focus driving operation due to
15 a force which is the sum of drive forces F_l and F_r generated in response to the currents I_l and I_r and shown in Fig. 21A and also which moves in the focus direction F , but also executes a tilt driving operation due to the moment $M = F_l \times d - F_r \times d$ that is generated around the center of gravity G of the
20 lens holder 201 due to the difference between the drive forces F_l and F_r . Here, d expresses the distance between the center of gravity G of the lens holder 201 and the focus coils 203fl, 203fr.

Now, Fig. 21B shows a case in which, differently from
25 Fig. 21A, the drive forces F_l and F_r are generated in the mutually

opposite directions. In this case, a force, which is going to move in the focus direction F, is $F_l + (-F_r)$, while a tilt is $F_l \times d - (-F_r \times d)$. At any rate, the objective lens drive apparatus executes a focus driving operation with a function of $(F_l + F_r)$ and executes a tilt driving operation with a function of $(F_l - F_r)$.

The left and right focus coils 203fl and 203fr not only can execute focus servo but also can adjust the inclination of the objective lens 202. Therefore, there is eliminated the need for provision of a coil and a magnet which are exclusively used to adjust the inclination of the objective lens 202. This can reduce the number of parts, can adjust the inclination of the objective lens 202 at a low cost, and can reduce the size of the whole objective lens drive apparatus.

In case where the tracking coil 203 is urged, due to the currents (shown by arrow marks in Fig. 19) that flow in the vertical sides A and C (which extend in parallel to the focus direction F) of the tracking coil 203t, there are generated drive forces in the same direction in the tracking direction T, so that the objective lens 202 can be moved in the tracking direction T according to the eccentricity of a record medium.

In case where the coil unit 203 is inserted into and bonded to the notch portions 201a of the lens holder 201, the number of magnetic gaps 205g can be reduced down to one. This can also reduce the number of parts, can adjust the inclination

of the objective lens 202 at a low cost, and can reduce the size of the whole objective lens drive apparatus.

In the above-mentioned embodiment, not only the focus servo but also the adjustment of the inclination of the objective lens 202 are carried out using the left and right focus coils 203fl and 203fr. However, a similar effect can also be obtained in the following structure: that is, as shown in Fig. 22, a coil unit 203 comprises a required number of printed circuit boards 203p which are laid one on top of another, while each of the printed circuit boards 203p includes a focus coil 203f and four tracking coils 203t; the focus coil 203f is arranged at the center of each printed circuit board 203p; the tracking coils 203tu and 203td are respectively disposed upwardly and downwardly of the objective-lens-optical-axis-direction center of gravity of a movable part including a lens holder 201 holding an objective lens 202, that is, the tracking coils 203tu and 203td are disposed in two right and left rows respectively extending upwardly and downwardly of the focus coil 203f; and, a magnet 205 is magnetized in two polarities in the focus direction by the boundary line 205b between the N and S poles of the magnet 205. In this structure, a magnetic circuit is similar to the magnetic circuit that is employed in the first embodiment and is shown in Fig. 2. By the way, the magnetic circuit may include one magnet 5' as shown in Fig. 9, and the coil unit may be disposed in the air gap 5g'. The magnetic

circuit is shown in Fig. 10, similar operation of coils when the magnetic circuit includes two magnets and the magnetic gap as described above can be obtained.

Here, alternatively, the tracking coils 203tu and 203td
5 may also be one in number respectively. Since currents are supplied to the upper and lower tracking coils 203tu and 203td individually, they are not connected in series but are connected independent of each other.

In this structure, the focus coil 203f and tracking coils
10 203tu, 203td are disposed on the same printed circuit board 203p. However, the focus coil 203f and tracking coils 203tu, 203td may also be disposed separately on two different printed circuit boards. In this case as well, the numbers of focus coils and tracking coils to be disposed on a printed circuit
15 board are respectively one and even.

The width W of the magnet 205 is determined such that,
at the movable neutral position of the movable part movably supported in a cantilevered manner by the conductive elastic members 204, that is, at the self-weight position of the movable
20 part in the focus direction F, as shown in Fig. 23, when the coil unit 203 is arranged within the magnetic gap 205g, the right and left inner vertical sides C and A of the vertical sides A and C (which extend in parallel to the focus direction) of the two upper-stage right and left tracking coils 203tu
25 as well as the two lower-stage right and left tracking coils

203td can be respectively disposed within the magnetic gap
205g (which points out a gap existing within the width W of
the mutually opposing magnets 205). Also, the height H of the
magnet 205 is determined such that, as shown in Fig. 23, not
5 only the horizontal sides b and d (which extend perpendicularly
to the focus direction F) of the focus coil 203f situated at
the center of the print circuit board 203p, but also the upper
sides D of the horizontal sides B and D (which extend
perpendicularly to the focus direction F) of the upper-stage
10 tracking coils 203tu and the lower sides B of the horizontal
sides B and D (which extend perpendicularly to the focus direction
F) of the lower-stage tracking coil 203td can be respectively
disposed within the magnetic gap 205g (which points out a gap
existing within the height W of the mutually opposing magnets
15 205).

The boundary line 205b between the N and S poles of the
magnet 205, as shown in Fig. 23, is situated midway not only
between the lower side b and upper side d of the horizontal
sides b and d (which extend perpendicularly to the focus direction
20 F) of the focus coil 203f but also between the lower sides
B of the horizontal sides B and D (which extend perpendicularly
to the focus direction F) of the upper-stage tracking coils
203tu and the upper sides D of the horizontal sides B and D
(which extend perpendicularly to the focus direction F) of
25 the lower-stage tracking coils 203td. And, the center of the

magnet 205 is substantially coincident with the center of the coil unit 203.

A tilt error signal and a tracking error signal, which have been obtained using an inclination detect sensor or using the reproduction signal of an optical pickup, are input to a control circuit which is similar to the control circuit shown in Fig. 20; and, the control circuit calculates the optimum currents I_u and I_d which can urge the tracking coils 203tu and 203td shown in Fig. 23 to thereby correct the tracking error and tilt error at the same time, and then the control circuit outputs the thus calculated currents I_u and I_d . The objective lens drive apparatus, which is an controlled object, not only executes a tracking driving operation due to a force which is the sum of driving forces (not shown) generated in response to the currents I_u and I_d and also which moves in the tracking direction F , but also executes a tilt driving operation due to the moment that is generated around the center of gravity of the lens holder 201 due to the difference between the driving forces.

In case where the focus coil 203f is urged, due to the currents (shown by arrow marks in Fig. 18) that flow in the horizontal sides b and d which extend perpendicularly to the focus direction F of the focus coil 203f in Fig. 18, there are generated driving forces in the same direction in the focus direction F , so that the objective lens 202 can be moved in

the focus direction F according to the surface vibration of the record medium.

Further, the system that can execute the tilt driving by the control unit having focus coil and tracking coil in the third embodiment can be applied to the objective lens drive apparatus according the second embodiment shown in Figs. 11 and 12.

As has been described heretofore, according to the first aspect of the invention, there is provided an objective lens drive apparatus in which a coil unit with a focus coil, a tracking coil and a tilt coil mounted thereon is disposed within the same magnetic gap of a magnetic circuit including at least one magnet. In the present objective lens drive apparatus, the inclination of an objective lens can be adjusted using the magnet for focus and tracking driving, which eliminates the need for provision of a magnet which is exclusively used to adjust the inclination of the objective lens. Therefore, according to the first aspect of the invention, it is possible to prevent an increase in the cost as well as an increase in the size of the objective lens drive apparatus, which are otherwise caused by the adjustment of the inclination of the objective lens.

Also, according to the second aspect of the invention, there is provided an objective lens drive apparatus in which there are completed two magnetic circuits each including at

least one magnet magnetized in two polarities and, within the magnetic gap of each of the two magnetic circuits, there is disposed a coil unit with a focus coil, a tracking coil and a tilt coil mounted thereon. In the present objective lens drive apparatus, the inclination of an objective lens can be adjusted using the magnets for focus and tracking driving, which eliminates the need for provision of a magnet which is exclusively used to adjust the inclination of the objective lens. Therefore, according to the second aspect of the invention, it is possible to prevent an increase in the cost of the objective lens drive apparatus as well as an increase in the size thereof, which are otherwise caused by the adjustment of the inclination of the objective lens.

Further, according to the third aspect of the invention, there is provided an objective lens drive apparatus in which a coil unit with a plurality of focus coils and a tracking coil mounted thereon is disposed within the same magnetic gap of a magnetic circuit including at least one magnet magnetized in two polarities, currents are supplied respectively to the plurality of focus coils included in the coil unit to thereby be able to execute focus servo due to the sum of drive forces generated in response to the supply of the currents, and moment is generated around the center of gravity of a movable part due to the difference between the drive forces to thereby be able to adjust the inclination of an objective lens simultaneously

with the focus servo. In the present objective lens drive apparatus, using the right and left focus coils, not only the focus servo but also the adjustment of the inclination of the objective lens can be carried out, which eliminates the need
5 for provision of a coil and a magnet which are exclusively used to adjust the inclination of the objective lens. Therefore, according to the third aspect of the invention, it is possible to prevent an increase in the cost of the objective lens drive apparatus as well as an increase in the size thereof, which
10 are otherwise caused by the adjustment of the inclination of the objective lens.